



浙江德清杰锋电气有限公司
ZHEJIANG·DEQINGJIEFENG ELECTRIC Co.,LTD

★Detailed technical specifications chart of AC fan
JF8025AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|---------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF8025A1HSL | 50/60 | 80*80*25MM | S | 110 | 0.14/0.12 | 15.4/13.2 | 2300/2700 | 17/21 | 3.0/4.3 | 29/33 | 230g |
| JF8025A1HBL | 50/60 | 80*80*25MM | B | 110 | 0.14/0.12 | 15.4/13.2 | 2400/2800 | 18/22 | 3.2/4.5 | 30/34 | |
| JF8025A2HSL | 50/60 | 80*80*25MM | S | 220 | 0.08/0.07 | 17.6/15.4 | 2300/2700 | 17/21 | 3.0/4.3 | 29/33 | |
| JF8025A2HBL | 50/60 | 80*80*25MM | B | 220 | 0.08/0.07 | 17.6/15.4 | 2400/2800 | 18/22 | 3.2/4.5 | 30/34 | |
| JF8025A3HSL | 50/60 | 80*80*25MM | S | 380 | 0.05/0.04 | 19.0/15.2 | 2300/2700 | 17/21 | 3.0/4.3 | 29/33 | |
| JF8025A3HBL | 50/60 | 80*80*25MM | B | 380 | 0.05/0.04 | 19.0/15.2 | 2400/2800 | 18/22 | 3.2/4.5 | 30/34 | |

JF8038AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|---------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF8038A1HSL | 50/60 | 80*80*38MM | S | 110 | 0.15/0.13 | 16.5/14.3 | 2300/2700 | 32/35 | 3.2/4.5 | 31/35 | 340g |
| JF8038A1HBL | 50/60 | 80*80*38MM | B | 110 | 0.15/0.13 | 16.5/14.3 | 2400/2800 | 33/36 | 3.4/4.9 | 32/36 | |
| JF8038A2HSL | 50/60 | 80*80*38MM | S | 220 | 0.07/0.06 | 15.4/13.2 | 2300/2700 | 32/35 | 3.2/4.5 | 31/35 | |
| JF8038A2HBL | 50/60 | 80*80*38MM | B | 220 | 0.07/0.06 | 15.4/13.2 | 2400/2800 | 33/36 | 3.4/4.9 | 32/36 | |
| JF8038A3HSL | 50/60 | 80*80*38MM | S | 380 | 0.04/0.03 | 15.2/11.4 | 2300/2700 | 32/35 | 3.2/4.5 | 31/35 | |
| JF8038A3HBL | 50/60 | 80*80*38MM | B | 380 | 0.04/0.03 | 15.2/11.4 | 2400/2800 | 33/36 | 3.4/4.9 | 32/36 | |

JF9225AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|---------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF9225A1HSL | 50/60 | 92*92*25MM | S | 110 | 0.14/0.12 | 15.4/13.2 | 2200/2600 | 25/31 | 2.3/3.3 | 36/40 | 270g |
| JF9225A1HBL | 50/60 | 92*92*25MM | B | 110 | 0.14/0.12 | 15.4/13.2 | 2250/2650 | 27/32 | 2.4/3.4 | 37/41 | |
| JF9225A2HSL | 50/60 | 92*92*25MM | S | 220 | 0.08/0.07 | 17.6/15.4 | 2200/2600 | 25/31 | 2.3/3.3 | 36/40 | |
| JF9225A2HBL | 50/60 | 92*92*25MM | B | 220 | 0.08/0.07 | 17.6/15.4 | 2250/2650 | 27/32 | 2.4/3.4 | 37/41 | |
| JF9225A3HSL | 50/60 | 92*92*25MM | S | 380 | 0.05/0.04 | 19.0/15.2 | 2200/2600 | 25/31 | 2.3/3.3 | 36/40 | |
| JF9225A3HBL | 50/60 | 92*92*25MM | B | 380 | 0.05/0.04 | 19.0/15.2 | 2250/2650 | 27/32 | 2.4/3.4 | 37/41 | |

JF9238AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|---------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF9238A1HSL | 50/60 | 92*92*38MM | S | 110 | 0.15/0.13 | 16.5/14.3 | 2400/2800 | 44/54 | 3.6/5.3 | 36/40 | 360g |
| JF9238A1HBL | 50/60 | 92*92*38MM | B | 110 | 0.15/0.13 | 16.5/14.3 | 2500/2900 | 45/55 | 3.7/5.5 | 37/41 | |
| JF9238A2HSL | 50/60 | 92*92*38MM | S | 220 | 0.07/0.06 | 15.4/13.2 | 2400/2800 | 44/54 | 3.6/5.3 | 36/40 | |
| JF9238A2HBL | 50/60 | 92*92*38MM | B | 220 | 0.07/0.06 | 15.4/13.2 | 2500/2900 | 45/55 | 3.7/5.5 | 37/41 | |
| JF9238A3HSL | 50/60 | 92*92*38MM | S | 380 | 0.04/0.03 | 15.2/11.4 | 2400/2800 | 44/54 | 3.6/5.3 | 36/40 | |
| JF9238A3HBL | 50/60 | 92*92*38MM | B | 380 | 0.04/0.03 | 15.2/11.4 | 2500/2900 | 45/55 | 3.7/5.5 | 37/41 | |

JF11025AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|--------------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF11025A1HSL | 50/60 | 110*110*25MM | S | 110 | 0.14/0.12 | 15.4/13.2 | 2150/2550 | 47/57 | 2.6/2.9 | 32/36 | 330g |
| JF11025A1HBL | 50/60 | 110*110*25MM | B | 110 | 0.14/0.12 | 15.4/13.2 | 2100/2600 | 48/58 | 2.7/3.0 | 34/38 | |
| JF11025A2HSL | 50/60 | 110*110*25MM | S | 220 | 0.08/0.07 | 17.6/15.4 | 2150/2550 | 47/57 | 2.6/2.9 | 32/36 | |
| JF11025A2HBL | 50/60 | 110*110*25MM | B | 220 | 0.08/0.07 | 17.6/15.4 | 2100/2600 | 48/58 | 2.7/3.0 | 34/38 | |
| JF11025A3HSL | 50/60 | 110*110*25MM | S | 380 | 0.05/0.04 | 19.0/15.2 | 2150/2550 | 47/57 | 2.6/2.9 | 32/36 | |
| JF11025A3HBL | 50/60 | 110*110*25MM | B | 380 | 0.05/0.04 | 19.0/15.2 | 2100/2600 | 48/58 | 2.7/3.0 | 34/38 | |

JF12025AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|--------------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF12025A1HSL | 50/60 | 120*120*25MM | S | 110 | 0.14/0.12 | 15.4/13.2 | 2000/2400 | 50/60 | 3.0/3.3 | 33/37 | 380g |
| JF12025A1HBL | 50/60 | 120*120*25MM | B | 110 | 0.14/0.12 | 15.4/13.2 | 2050/2450 | 51/61 | 3.1/3.4 | 34/38 | |
| JF12025A2HSL | 50/60 | 120*120*25MM | S | 220 | 0.08/0.07 | 17.6/15.4 | 2150/2400 | 50/60 | 3.0/3.3 | 33/37 | |
| JF12025A2HBL | 50/60 | 120*120*25MM | B | 220 | 0.08/0.07 | 17.6/15.4 | 2050/2450 | 51/61 | 3.1/3.4 | 34/38 | |
| JF12025A3HSL | 50/60 | 120*120*25MM | S | 380 | 0.05/0.04 | 19.0/15.2 | 2000/2400 | 50/60 | 3.0/3.3 | 33/37 | |
| JF12025A3HBL | 50/60 | 120*120*25MM | B | 380 | 0.05/0.04 | 19.0/15.2 | 2050/2450 | 51/61 | 3.1/3.4 | 34/38 | |

JF12038AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|--------------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF12038A1HSL | 50/60 | 120*120*38MM | S | 110 | 0.24/0.21 | 26.4/23.1 | 2600/3000 | 75/90 | 6.3/7.3 | 44/46 | 550g |
| JF12038A1HBL | 50/60 | 120*120*38MM | B | 110 | 0.24/0.21 | 26.4/23.1 | 2600/3000 | 77/92 | 6.6/7.5 | 45/47 | |
| JF12038A2HSL | 50/60 | 120*120*38MM | S | 220 | 0.14/0.10 | 30.8/22.0 | 2600/3000 | 75/90 | 6.3/7.3 | 44/46 | |
| JF12038A2HBL | 50/60 | 120*120*38MM | B | 220 | 0.14/0.10 | 30.8/22.0 | 2600/3000 | 77/92 | 6.6/7.5 | 45/47 | |
| JF12038A3HSL | 50/60 | 120*120*38MM | S | 380 | 0.08/0.07 | 30.4/26.6 | 2600/3000 | 75/90 | 6.3/7.3 | 44/46 | |
| JF12038A3HBL | 50/60 | 120*120*38MM | B | 380 | 0.08/0.07 | 30.4/26.6 | 2600/3000 | 77/92 | 6.6/7.5 | 45/47 | |
| JF12038A1LSL | 50/60 | 120*120*38MM | S | 110 | 0.15/0.14 | 16.5/15.4 | 1800/1900 | 46/53 | 3.6/4.5 | 35/38 | |
| JF12038A1LBL | 50/60 | 120*120*38MM | B | 110 | 0.15/0.14 | 16.5/15.4 | 1850/2000 | 47/54 | 3.6/4.5 | 37/40 | |
| JF12038A2LSL | 50/60 | 120*120*38MM | S | 220 | 0.08/0.07 | 17.6/15.4 | 1800/1900 | 46/53 | 3.6/4.5 | 35/38 | |
| JF12038A2LBL | 50/60 | 120*120*38MM | B | 220 | 0.08/0.07 | 17.6/15.4 | 1850/2000 | 47/54 | 3.6/4.5 | 37/40 | |
| JF12038A3LSL | 50/60 | 120*120*38MM | S | 380 | 0.05/0.04 | 19.0/15.2 | 1800/1900 | 46/53 | 3.6/4.5 | 35/38 | |
| JF12038A3LBL | 50/60 | 120*120*38MM | B | 380 | 0.05/0.04 | 19.0/15.2 | 1850/2000 | 47/54 | 3.6/4.5 | 37/40 | |

JF15050AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|--------------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF15050A1HSL | 50/60 | 150*150*50MM | S | 110 | 0.43/0.39 | 47.3/42.9 | 2300/2500 | 150/190 | 11/13 | 52/53 | 950g |
| JF15050A1HBL | 50/60 | 150*150*50MM | B | 110 | 0.43/0.39 | 47.3/42.9 | 2350/2500 | 150/190 | 11/13 | 53/54 | |
| JF15050A2HSL | 50/60 | 150*150*50MM | S | 220 | 0.24/0.21 | 52.8/46.2 | 2300/2500 | 150/190 | 11/13 | 52/53 | |
| JF15050A2HBL | 50/60 | 150*150*50MM | B | 220 | 0.24/0.21 | 59.4/50.6 | 2350/2500 | 150/190 | 11/13 | 53/54 | |
| JF15050A3HSL | 50/60 | 150*150*50MM | S | 380 | 0.12/0.10 | 45.6/38.0 | 2300/2500 | 150/190 | 11/13 | 52/53 | |
| JF15050A3HBL | 50/60 | 150*150*50MM | B | 380 | 0.12/0.10 | 45.6/38.0 | 2350/2500 | 150/190 | 11/13 | 53/54 | |

FZY150 AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|-----------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| FZY150-2D | 50/60 | 150*150*50MM | B | 220 | 0.32/0.28 | 60.00 | 2500 | 180 | 3/250 | 60 | 1000g |
| FZY150-2D | 50/60 | 150*150*50MM | B | 220 | 0.32/0.28 | 60.00 | 2500 | 90 | 0.47/400 | 40 | |
| FZY150-4D | 50/60 | 150*150*50MM | B | 380 | 0.24/0.21 | 63.00 | 2400 | 180 | 1/400 | 60 | |
| FZY150-4D | 50/60 | 150*150*50MM | B | 380 | 0.24/0.21 | 63.00 | 2400 | 90 | - | 40 | |

JF17051AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|--------------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF17051A1HSL | 50/60 | 170*170*51MM | S | 110 | 0.43/0.39 | 47.3/42.9 | 2300/2500 | 150/190 | 11/13 | 52/53 | 1000g |
| JF17051A1HBL | 50/60 | 170*170*51MM | B | 110 | 0.43/0.39 | 47.3/42.9 | 2350/2500 | 150/190 | 11/13 | 53/54 | |
| JF17051A2HSL | 50/60 | 170*170*51MM | S | 220 | 0.24/0.21 | 52.8/46.2 | 2300/2500 | 150/190 | 11/13 | 52/53 | |
| JF17051A2HBL | 50/60 | 170*170*51MM | B | 220 | 0.24/0.21 | 59.4/50.6 | 2350/2500 | 150/190 | 11/13 | 53/54 | |
| JF17051A3HSL | 50/60 | 170*170*51MM | S | 380 | 0.12/0.10 | 45.6/38.0 | 2300/2500 | 150/190 | 11/13 | 52/53 | |
| JF17051A3HBL | 50/60 | 170*170*51MM | B | 380 | 0.12/0.10 | 45.6/38.0 | 2350/2500 | 150/190 | 11/13 | 53/54 | |

JF17251AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|--------------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF17251A1HSL | 50/60 | 170*170*51MM | S | 110 | 0.43/0.39 | 47.3/42.9 | 2300/2500 | 150/190 | 11/13 | 52/53 | 1000g |
| JF17251A1HBL | 50/60 | 170*170*51MM | B | 110 | 0.43/0.39 | 47.3/42.9 | 2350/2500 | 150/190 | 11/13 | 53/54 | |
| JF17251A2HSL | 50/60 | 170*170*51MM | S | 220 | 0.24/0.21 | 52.8/46.2 | 2300/2500 | 150/190 | 11/13 | 52/53 | |
| JF17251A2HBL | 50/60 | 170*170*51MM | B | 220 | 0.24/0.21 | 59.4/50.6 | 2350/2500 | 150/190 | 11/13 | 53/54 | |
| JF17251A3HSL | 50/60 | 170*170*51MM | S | 380 | 0.12/0.10 | 45.6/38.0 | 2300/2500 | 150/190 | 11/13 | 52/53 | |
| JF17251A3HBL | 50/60 | 170*170*51MM | B | 380 | 0.12/0.10 | 45.6/38.0 | 2350/2500 | 150/190 | 11/13 | 53/54 | |

JF20060AC

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|-------|---------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
|-------|---------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|

| | | | | | | | | | | | |
|--------------|-------|--------------|---|-----|-----------|-------|-----------|---------|-------|-------|-------|
| JF20060A1HBL | 50/60 | 200*200*60MM | B | 110 | 0.58/0.50 | 56/54 | 2100/2300 | 170/180 | 17/19 | 64/66 | 1700g |
| JF20060A2HBL | 50/60 | 200*200*60MM | B | 220 | 0.31/0.30 | 56/54 | 2300/2500 | 180/190 | 18/20 | 65/68 | |
| JF20060A3HBL | 50/60 | 200*200*60MM | B | 380 | 0.15/0.16 | 65/63 | 2400/2600 | 190/200 | 20/22 | 67/69 | |

FZY200

Specification Table:

| Model | Freq Hz | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ₂ O | Noise dBA | Weight |
|-----------|---------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| FZY200-2D | 50/60 | 210*210*70MM | B | 220 | 0.15 | 25.00 | 1200 | 6.5 | 11/13 | 60 | 2000g |
| FZY200-2D | 50/60 | 210*210*70MM | B | 220 | 0.30 | 65.00 | 2300 | 13 | 15/17 | 70 | |
| FZY200-4D | 50/60 | 210*210*70MM | B | 380 | 0.08 | 25.00 | 1200 | 6.5 | 11/13 | 60 | |
| FZY200-4D | 50/60 | 210*210*70MM | B | 380 | 0.18 | 65.00 | 2300 | 13 | 15/17 | 70 | |



浙江德清杰锋电气有限公司
ZHEJIANG·DEQINGJIEFENG ELECTRIC Co.,LTD

★Detailed technical specifications chart of direct current fan
JF2510DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF2510D5HS | 25*25*10MM | Sleeve Ball | 5 | 0.18 | 0.90 | 10000 | 2.00 | 3.6 | 24 | 8g |
| JF2510D5MS | 25*25*10MM | | 5 | 0.14 | 0.70 | 7000 | 1.60 | 2 | 22 | |
| JF2510D12HS | 25*25*10MM | | 12 | 0.09 | 1.08 | 10000 | 2.00 | 3.6 | 24 | |
| JF2510D12MS | 25*25*10MM | | 12 | 0.07 | 0.84 | 7000 | 1.60 | 2 | 22 | |

JF3010DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF3010D5HS | 30*30*10MM | Sleeve Ball | 5 | 0.19 | 0.95 | 10000 | 4.40 | 4.50 | 22 | 9g |
| JF3010D5MS | 30*30*10MM | | 5 | 0.15 | 0.75 | 9000 | 3.40 | 2.40 | 18.7 | |
| JF3010D12HS | 30*30*10MM | | 12 | 0.10 | 1.20 | 10000 | 4.40 | 4.50 | 22 | |
| JF3010D12MS | 30*30*10MM | | 12 | 0.08 | 0.96 | 9000 | 3.40 | 2.40 | 18.7 | |

JF4020DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF4020D5HS | 40*40*20MM | Sleeve Ball | 5 | 0.28 | 1.40 | 7500 | 8.60 | 5.55 | 34.5 | 27g |
| JF4020D5MS | 40*40*20MM | | 5 | 0.20 | 1.00 | 5000 | 5.70 | 2.50 | 23.9 | |
| JF4020D12HS | 40*40*20MM | | 12 | 0.12 | 1.44 | 7500 | 8.60 | 5.55 | 34.5 | |

JF5015DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF5015D12HS | 50*50*15MM | Sleeve Ball | 12 | 0.13 | 1.56 | 5000 | 14.70 | 4.10 | 31 | 27g |
| JF5015D12MS | 50*50*15MM | | 12 | 0.11 | 1.44 | 4500 | 13.80 | 3.40 | 28.4 | |
| JF5015D12LS | 50*50*15MM | | 12 | 0.08 | 0.96 | 3800 | 12.40 | 2.80 | 25.9 | |

JF6025DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF6025D12HS | 60*60*25MM | Sleeve Ball | 12 | 0.16 | 1.92 | 4500 | 23.50 | 5.60 | 29.9 | 62g |
| JF6025D12MS | 60*60*25MM | | 12 | 0.13 | 1.56 | 3900 | 21.50 | 4.20 | 25.8 | |
| JF6025D12LS | 60*60*25MM | | 12 | 0.08 | 0.96 | 3500 | 19.30 | 3.40 | 21.5 | |
| JF6025D24HS | 60*60*25MM | | 24 | 0.16 | 3.12 | 4500 | 23.50 | 5.60 | 29.9 | |
| JF6025D24MS | 60*60*25MM | | 24 | 0.13 | 1.68 | 3900 | 21.50 | 4.20 | 25.8 | |

JF7025DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF7025D12HS | 70*70*25MM | Sleeve Ball | 12 | 0.23 | 2.76 | 3100 | 45.60 | 4.90 | 33.5 | 65g |
| JF7025D12MS | 70*70*25MM | | 12 | 0.15 | 1.80 | 2500 | 38.10 | 3.10 | 27.9 | |
| JF7025D12LS | 70*70*25MM | | 12 | 0.12 | 1.44 | 2200 | 33.80 | 2.70 | 25.0 | |
| JF7025D24HS | 70*70*25MM | | 24 | 0.12 | 2.88 | 3100 | 45.60 | 4.90 | 33.5 | |
| JF7025D24MS | 70*70*25MM | | 24 | 0.07 | 1.68 | 2500 | 38.10 | 3.10 | 27.9 | |

JF8025DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF8025D12HS | 80*80*25MM | Sleeve Ball | 12 | 0.25 | 3.00 | 3010 | 38.30 | 3.60 | 34.0 | 75g |
| JF8025D12MS | 80*80*25MM | | 12 | 0.15 | 1.80 | 2440 | 31.30 | 2.50 | 28.4 | |
| JF8025D12LS | 80*80*25MM | | 12 | 0.12 | 1.44 | 2030 | 26.10 | 1.60 | 22.4 | |
| JF8025D24HS | 80*80*25MM | | 24 | 0.16 | 3.84 | 3010 | 38.30 | 3.60 | 34.0 | |
| JF8025D24MS | 80*80*25MM | | 24 | 0.10 | 2.40 | 2440 | 31.30 | 2.50 | 28.4 | |
| JF8025D24LS | 80*80*25MM | | 24 | 0.09 | 2.16 | 2030 | 26.10 | 1.60 | 22.4 | |

JF9225DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|-------------|------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF9225D12HS | 92*92*25MM | Sleeve Ball | 12 | 0.15 | 3.00 | 2300 | 14.60 | 4.80 | 34.6 | 87g |
| JF9225D12MS | 92*92*25MM | | 12 | 0.18 | 3.36 | 2000 | 15.30 | 5.00 | 35.0 | |
| JF9225D12LS | 92*92*25MM | | 12 | 0.13 | 3.36 | 2200 | 17.60 | 6.20 | 39.5 | |
| JF9225D24HS | 92*92*25MM | | 24 | 0.15 | 3.60 | 2300 | 14.60 | 4.80 | 34.6 | |
| JF9225D24MS | 92*92*25MM | | 24 | 0.18 | 4.32 | 2000 | 15.30 | 5.00 | 35.0 | |
| JF9225D24LS | 92*92*25MM | | 24 | 0.18 | 4.32 | 2200 | 17.60 | 6.20 | 39.5 | |

JF12025DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|--------------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF12025D12US | 120*120*25MM | Sleeve Ball | 12 | 0.50 | 6.00 | 2500 | 98.60 | 6.20 | 43.3 | 160g |
| JF12025D12HS | 120*120*25MM | | 12 | 0.37 | 4.44 | 2200 | 85.30 | 4.70 | 39.0 | |
| JF12025D12MS | 120*120*25MM | | 12 | 0.33 | 3.96 | 2050 | 80.50 | 3.70 | 38.0 | |
| JF12025D24HS | 120*120*25MM | | 24 | 0.24 | 5.75 | 2200 | 85.20 | 4.70 | 39.1 | |
| JF12025D24MS | 120*120*25MM | | 24 | 0.20 | 4.80 | 2050 | 80.50 | 3.70 | 38.0 | |

JF12038DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|--------------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF12038D12US | 120*120*38MM | Sleeve Ball | 12 | 2.30 | 15.00 | 5000 | 178.00 | 11.90 | 53.9 | 230g |
| JF12038D12HS | 120*120*38MM | | 12 | 1.00 | 12.00 | 3000 | 124.80 | 8.60 | 48.8 | |
| JF12038D12MS | 120*120*38MM | | 12 | 0.50 | 6.00 | 2540 | 94.00 | 7.00 | 41.0 | |
| JF12038D12LS | 120*120*38MM | | 12 | 0.35 | 4.20 | 1950 | 72.30 | 4.90 | 32.9 | |
| JF12038D24HS | 120*120*38MM | | 24 | 0.50 | 12.00 | 2950 | 118.80 | 8.60 | 48.8 | |
| JF12038D24MS | 120*120*38MM | | 24 | 0.32 | 7.68 | 2540 | 94.00 | 7.00 | 41.0 | |
| JF12038D24LS | 120*120*38MM | | 24 | 0.25 | 6.00 | 2000 | 77.50 | 4.90 | 33.6 | |
| JF12038D48HS | 120*120*38MM | | 48 | 0.25 | 11.00 | 2950 | 118.80 | 7.60 | 48.8 | |
| JF12038D48MS | 120*120*38MM | | 48 | 0.14 | 6.72 | 2540 | 94.00 | 6.00 | 41.0 | |

JF17250DC

Specification Table:

| Model | Measure MM | Bearing Style | Voltage VAC | Current AMP | Power Watt | Speed RPM | Airflow CFM | Pressure mm H ² O | Noise dBA | Weight |
|--------------|--------------|---------------|-------------|-------------|------------|-----------|-------------|------------------------------|-----------|--------|
| JF17250D12HB | 172*150*50MM | Sleeve Ball | 12 | 1.40 | 18.00 | 3000 | 203.00 | 15.50 | 52.6 | 850g |
| JF17250D12MB | 172*150*50MM | | 12 | 0.85 | 10.80 | 2600 | 177.50 | 11.80 | 47.9 | |
| JF17250D24HB | 172*150*50MM | | 24 | 0.65 | 16.00 | 2900 | 201.50 | 14.40 | 51.8 | |
| JF17250D24MB | 172*150*50MM | | 24 | 0.44 | 10.50 | 2500 | 174.00 | 10.40 | 47.0 | |
| JF17250D48HB | 172*150*50MM | | 48 | 0.35 | 16.80 | 2900 | 201.50 | 14.40 | 51.8 | |
| JF17250D48MB | 172*150*50MM | | 48 | 0.25 | 12.00 | 2600 | 177.50 | 11.80 | 47.9 | |